



# Heavy Duty EXTENDED SERVICE INTERVAL

SCA PRE-CHARGED



**Learn More** about our technology on the back

**Detroit Diesel® Certified - 93K217**

See all OEM listings below

✓ **Protects Against Rust & Corrosion**

✓ **Low Silicate Formula**

✓ **No Phosphates**

✓ **For use in:**

- Heavy & Medium Duty Vehicles - Classes 6-8
- Aluminum & Cast Iron Components
- Diesel Engines & Natural Gas Engines

**Meets or Exceeds OEM Performance Requirements:**

Cummins CES 14439	Navistar CEMS B-1, Type II
Cummins CES 90T8-4	Freightliner 48-22880
<b>Detroit Diesel 93K217</b>	Kenworth R026-170-97
Detroit Diesel 7SE298	Peterbilt 8502.002
Mack 014617004	John Deere H24, H24 A1
Freightliner 48-25961	John Deere JDS-G135
Freightliner 48-25878	John Deere 8650-5

**Meets or Exceeds Industry & Governmental Standards:**

<b>ASTM D6210</b>	ASTM D4340	TMC RP329A	SAE J1034
ASTM D3306	GCA A-A-52624	TMC RP338A	SAE J1941
<b>ASTM D4985</b>	CID A-A-52624A	TMC RP351	



# Heavy Duty EXTENDED SERVICE INTERVAL SCA PRE-CHARGED

CONCENTRATE	PACK	UPC	READY TO USE	PACK	UPC
AFC10000	6/1 gal.	7 97496-87765 9	AFC10100	6/1 gal.	7 97496-87769 7
AFC10000-55	55 gal. drum	7 97496-87766 6	AFC10100-55	55 gal. drum	7 97496-87770 3
AFC10000-1KL	264 gal. tote	7 97496-87767 3	AFC10100-1KL	264 gal. tote	7 97496-87774 1

## AFC10000 TECHNICAL DATA

Composition by Weight	Typical Values
Antifreeze/Coolant Concentrate:	96.8%
Total Water:	3.2%
Dyes:	Trace

Properties	Typical Values	Tests
Color:	Purple/Fuchsia	
Odor:	Characteristic	
Ash Content:	0.50% by weight	Federal #209B
pH at 50 vol%:	10.9	ASTM D1287
Reserve Alkalinity:	5.7 mL	ASTM D1121
Density at 15°C, g/mL:	1.1189	ASTM D1122
Freezing Point at 50 vol%:	-34°F (-37°C)	ASTM D1177
Boiling Point at 50 vol%: <i>Under standard pressure</i>	+226°F (+108°C)	ASTM D1120
Foam Test:	20 mL/0.6 sec.	ASTM D1881

## AFC10100 TECHNICAL DATA

Composition by Weight	Typical Values
Antifreeze/Coolant Concentrate:	52.3%
Total Water:	47.7%
Dyes:	Trace

Properties	Typical Values	Tests
Color:	Purple/Fuchsia	
Odor:	Characteristic	
Ash Content:	0.34% by weight	Federal #209B
pH:	10.9	ASTM D1287
Reserve Alkalinity:	2.8 mL	ASTM D1121
Density at 15°C, g/mL:	1.0724	ASTM D1122
Freezing Point:	-34°F (-37°C)	ASTM D1177
Boiling Point: <i>Under standard pressure</i>	+226°F (+108°C)	ASTM D1120
Foam Test:	20 mL/0.6 sec.	ASTM D1881

Most of our PRESTONE COMMAND® Antifreeze+Coolant Products come in 55 Gal. Drums, 264 Gal. Totes and Bulk.



55 gal. drum

264 gal. tote