

Prestone® Antifreeze/Coolant with Leak Detect

Version number: 1.0

Date of compilation: 2025-04-29

SECTION 1: Identification**1.1 Product identifier**

Trade name

Prestone® Antifreeze/Coolant with Leak Detect

1.1.7 Other means of identification

SDS967

1.1.7.2 Product number

AF2150

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Coolant
Professional use
Industrial use
Consumer use (private households)**1.3 Details of the supplier of the safety data sheet**

Prestone Products Corporation

69 Eagle Rd.

CT 06810 Danbury

United States

Telephone: (888)269-0750 (in the US and Canada), 01-800-715-4135 (in Mexico)

1.4 Emergency telephone number

Emergency information service

CHEMTREC 1-800-424-9300 (in the US and Canada) +1 703 741-5970 (outside the US and Canada)
24 hour emergency number**SECTION 2: Hazard(s) identification****2.1 Classification of the substance or mixture**

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Section	Hazard class	Category	Hazard class and category	Hazard statement
A.10	acute toxicity (oral)	4	Acute Tox. 4	H302
A.7	reproductive toxicity	1B	Repr. 1B	H360D
A.9	specific target organ toxicity - repeated exposure	2	STOT RE 2	H373

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects

Delayed or immediate effects can be expected after short or long-term exposure.

2.2 Label elements

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

- Signal word danger

- Pictograms

GHS07, GHS08



Prestone® Antifreeze/Coolant with Leak Detect

Version number: 1.0

Date of compilation: 2025-04-29

- Hazard statements

H302 Harmful if swallowed.
H360D May damage the unborn child.
H373 May cause damage to organs through prolonged or repeated exposure.

- Precautionary statements

P201 Obtain special instructions before use.
P260 Do not breathe dust/fume/gas/mist/vapors/spray.
P270 Do not eat, drink or smoke when using this product.
P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P301+P312 If swallowed: Call a poison center/doctor if you feel unwell.
P308+P313 If exposed or concerned: Get medical advice/attention.
P314 Get medical advice/attention if you feel unwell.
P330 Rinse mouth.
P405 Store locked up.
P501 Dispose of contents/container to industrial combustion plant.

- Hazardous ingredients for labelling

ethylene glycol, 2-ethylhexanoic acid, Diethylene Glycol

2.3 Other hazards**Results of PBT and vPvB assessment**Does not contain a PBT-/vPvB-substance at a concentration of $\geq 0.1\%$.**Endocrine disrupting properties**Does not contain an endocrine disruptor (ED) in a concentration of $\geq 0.1\%$.**SECTION 3: Composition/information on ingredients****3.1 Substances**

Not relevant (mixture)

3.2 Mixtures**Description of the mixture**

Name of substance	Identifier	Wt%	Classification acc. to GHS
ethylene glycol	CAS No 107-21-1	40 - < 55	Acute Tox. 4 / H302 STOT RE 2 / H373
Diethylene Glycol	CAS No 111-46-6	1 - < 5	Acute Tox. 4 / H302 Acute Tox. 4 / H332
2-ethylhexanoic acid	CAS No 149-57-5	1 - < 5	Repr. 1B / H360D

Hazardous ingredients, Consideration of other advice

This table, if present, includes all GHS classified ingredients present above their cut-off limits, even if the finished product is not classified as hazardous by GHS.

Exact percentage of ingredients is withheld as a trade secret.

Remarks

For full text of abbreviations: see SECTION 16.

Prestone® Antifreeze/Coolant with Leak Detect

Version number: 1.0

Date of compilation: 2025-04-29

SECTION 4: First-aid measures**4.1 Description of first-aid measures****General notes**

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Fire-fighting measures**5.1 Extinguishing media****Suitable extinguishing media**

Water spray, Alcohol resistant foam, BC-powder, Carbon dioxide (CO2)

Unsuitable extinguishing media

Water jet

5.2 Special hazards arising from the substance or mixture**Hazardous combustion products**

Carbon monoxide (CO), Carbon dioxide (CO2)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures****For non-emergency personnel**

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

6.3 Methods and material for containment and cleaning up**Advice on how to contain a spill**

Covering of drains

Prestone® Antifreeze/Coolant with Leak Detect

Version number: 1.0

Date of compilation: 2025-04-29

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage**7.1 Precautions for safe handling****Recommendations****- Measures to prevent fire as well as aerosol and dust generation**

Use local and general ventilation. Use only in well-ventilated areas.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities**Control of the effects****Protect against external exposure, such as**

frost

7.3 Specific end use(s)

See section 16 for a general overview.

SECTION 8: Exposure controls/personal protection**8.1 Control parameters**

Occupational exposure limit values (Workplace Exposure Limits)											
Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Ceiling-C [ppm]	Ceiling-C [mg/m ³]	Notation	Source
US	ethylene glycol	107-21-1	REL							appxD	NIOSH REL
US	ethylene glycol	107-21-1	TLV®				10			i, aerosol	AC-GIH® 2024
US	ethylene glycol	107-21-1	PEL (CA)					40	100	vap	Cal/OSHA PEL
US	ethylene glycol	107-21-1	TLV®	25		50				vap	AC-GIH® 2024
US	2-ethylhexanoic acid	149-57-5	TLV®		5					iv	AC-GIH® 2024

Prestone® Antifreeze/Coolant with Leak Detect

Version number: 1.0

Date of compilation: 2025-04-29

Notation

aerosol	as aerosols
appx-D	see Appendix D - Substances with No Established RELs
Ceiling-C	ceiling value is a limit value above which exposure should not occur
i	inhalable fraction
iv	inhalable fraction and vapor
STEL	short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)
TWA	time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)
vap	as vapors

Relevant DNELs of components						
Name of substance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
ethylene glycol	107-21-1	DNEL	35 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects
ethylene glycol	107-21-1	DNEL	106 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
Diethylene Glycol	111-46-6	DNEL	44 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
Diethylene Glycol	111-46-6	DNEL	60 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects
Diethylene Glycol	111-46-6	DNEL	43 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
2-ethylhexanoic acid	149-57-5	DNEL	14 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
2-ethylhexanoic acid	149-57-5	DNEL	2 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects

Relevant PNECs of components						
Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
ethylene glycol	107-21-1	PNEC	10 mg/l	aquatic organisms	freshwater	short-term (single instance)
ethylene glycol	107-21-1	PNEC	1 mg/l	aquatic organisms	marine water	short-term (single instance)
ethylene glycol	107-21-1	PNEC	199.5 mg/l	microorganisms	sewage treatment plant (STP)	short-term (single instance)
ethylene glycol	107-21-1	PNEC	37 mg/kg	benthic organisms	sediment	short-term (single instance)
ethylene glycol	107-21-1	PNEC	3.7 mg/kg	pelagic organisms	sediment	short-term (single instance)
ethylene glycol	107-21-1	PNEC	1.53 mg/kg	terrestrial organisms	soil	short-term (single instance)
ethylene glycol	107-21-1	PNEC	10 mg/l	aquatic organisms	water	intermittent release
Diethylene Glycol	111-46-6	PNEC	10 mg/l	aquatic organisms	freshwater	short-term (single instance)
Diethylene Glycol	111-46-6	PNEC	1 mg/l	aquatic organisms	marine water	short-term (single instance)

Prestone® Antifreeze/Coolant with Leak Detect

Version number: 1.0

Date of compilation: 2025-04-29

Relevant PNECs of components						
Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
Diethylene Glycol	111-46-6	PNEC	199.5 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
Diethylene Glycol	111-46-6	PNEC	20.9 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
Diethylene Glycol	111-46-6	PNEC	2.09 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
Diethylene Glycol	111-46-6	PNEC	1.53 mg/kg	terrestrial organisms	soil	short-term (single instance)
2-ethylhexanoic acid	149-57-5	PNEC	0.398 mg/l	aquatic organisms	freshwater	short-term (single instance)
2-ethylhexanoic acid	149-57-5	PNEC	0.04 mg/l	aquatic organisms	marine water	short-term (single instance)
2-ethylhexanoic acid	149-57-5	PNEC	4.74 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
2-ethylhexanoic acid	149-57-5	PNEC	0.474 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
2-ethylhexanoic acid	149-57-5	PNEC	0.712 mg/kg	terrestrial organisms	soil	short-term (single instance)
2-ethylhexanoic acid	149-57-5	PNEC	72 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

Prestone® Antifreeze/Coolant with Leak Detect

Version number: 1.0

Date of compilation: 2025-04-29

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties****Appearance**

Physical state	liquid
Color	brown
Particle	not relevant (liquid)
Odor	characteristic

Other safety parameters

pH (value)	8.6 (25 °C)
Melting point/freezing point	<-37 °C / <-34 °F
Initial boiling point and boiling range	108 °C / 226 °F
Flash point	>102.2 °C / >216 °F closed cup
Evaporation rate	Not determined
Flammability (solid, gas)	not relevant, (fluid)
Vapor pressure	<0.1 mmHg at 68 °F
Density	1.069 g/cm³ at 20 °C
Vapor density	this information is not available

Solubility(ies)

- Water solubility	miscible in any proportion
--------------------	----------------------------

Partition coefficient

- n-octanol/water (log KOW)	this information is not available
Auto-ignition temperature	372 °C (auto-ignition temperature (liquids and gases))

Viscosity

- Kinematic viscosity	2.807 mm²/s at 20 °C
- Dynamic viscosity	3 mPa s at 20 °C
Explosive properties	none
Oxidizing properties	none
Temperature class (USA, acc. to NEC 500)	T2 (maximum permissible surface temperature on the equipment: 300°C)

Prestone® Antifreeze/Coolant with Leak Detect

Version number: 1.0

Date of compilation: 2025-04-29

SECTION 10: Stability and reactivity**10.1 Reactivity**

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials".

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

There are no specific conditions known which have to be avoided.

10.5 Incompatible materials

Oxidizers

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information**11.1 Information on toxicological effects**

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)**Acute toxicity**

Harmful if swallowed.

- Acute toxicity estimate (ATE)

Oral 996 mg/kg

Acute toxicity estimate (ATE) of components

Name of substance	CAS No	Exposure route	ATE
ethylene glycol	107-21-1	oral	500 mg/kg
ethylene glycol	107-21-1	dermal	>3,500 mg/kg
Diethylene Glycol	111-46-6	oral	500 mg/kg
Diethylene Glycol	111-46-6	inhalation: vapor	11 mg/1/4h
Diethylene Glycol	111-46-6	inhalation: dust/mist	>4.6 mg/1/4h
2-ethylhexanoic acid	149-57-5	oral	2,043 mg/kg
2-ethylhexanoic acid	149-57-5	dermal	>2,000 mg/kg

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitization

Shall not be classified as a respiratory or skin sensitizer.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Prestone® Antifreeze/Coolant with Leak Detect

Version number: 1.0

Date of compilation: 2025-04-29

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

May damage the unborn child.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

SECTION 12: Ecological information**12.1 Toxicity**

Shall not be classified as hazardous to the aquatic environment.

12.2 Persistence and degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Does not contain a PBT-/vPvB-substance at a concentration of $\geq 0.1\%$.

12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) in a concentration of $\geq 0.1\%$.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations**13.1 Waste treatment methods****Sewage disposal-relevant information**

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport information**14.1 UN number**

not subject to transport regulations

14.2 UN proper shipping name

not relevant

14.3 Transport hazard class(es)

none

14.4 Packing group

not assigned

14.5 Environmental hazards

non-environmentally hazardous acc. to the dangerous goods regulations



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Prestone® Antifreeze/Coolant with Leak Detect

Version number: 1.0

Date of compilation: 2025-04-29

14.6 Special precautions for user

There is no additional information.

14.7 Transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

Information for each of the UN Model Regulations

Transport of dangerous goods by road or rail (49 CFR US DOT) - Additional information

Not subject to transport regulations.

Note: IF A SHIPMENT OF A REPORTABLE QUANTITY (8,333 LBS/933 GAL.) IN A SINGLE PACKAGE IS INVOLVED, THE FOLLOWING INFORMATION APPLIES:

PROPER SHIPPING NAME:

RQ, Environmentally hazardous substance, liquid, n.o.s. (Ethylene glycol)

UN NUMBER: UN3082

PACKING GROUP: III

LABELS REQUIRED: Class 9

International Maritime Dangerous Goods Code (IMDG) - Additional information

Not subject to IMDG.

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Not subject to ICAO-IATA.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

National regulations (United States)

Toxic Substance Control Act (TSCA)

all ingredients are listed (ACTIVE) or exempt from listing

Superfund Amendment and Reauthorization Act (SARA TITLE III)

- The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Section 302, 304)

none of the ingredients are listed

- Specific Toxic Chemical Listings (EPCRA Section 313)

Toxics Release Inventory: Specific Toxic Chemical Listings

Name of substance	CAS No	Remarks	Effective date
ethylene glycol	107-21-1		1987-01-01

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)

- List of Hazardous Substances and Reportable Quantities (CERCLA section 102a) (40 CFR 302.4)

Name of substance	CAS No	Remarks	Statutory code	Final RQ pounds (Kg)
ethylene glycol	107-21-1		3	5000 (2270)

Legend

3 "3" indicates that the source is section 112 of the Clean Air Act

Clean Air Act

none of the ingredients are listed



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Prestone® Antifreeze/Coolant with Leak Detect

Version number: 1.0

Date of compilation: 2025-04-29

Right to Know Hazardous Substance List

- Cleaning Product Right to Know Act Substance List (CA-RTK)

Name of substance	CAS No	Functionality	Authoritative Lists
ethylene glycol	107-21-1	alcohols	CA NLS CA TACs NTP OHAT - Repr. or Dev. Toxicants OEHHA RELs Prop 65
Diethylene Glycol			CA TACs
propylene glycol	57-55-6	humectant	
Phosphoric acid (residual)	7664-38-2		OEHHA RELs
sodium polyacrylate	9003-04-7	chelate / sequestrant	

- Toxic or Hazardous Substance List (MA-TURA)

Name of substance	CAS No	DEP CODE	PBT / HHS / LHS	PBT / HHS Threshold	De Minimis Concentration Threshold
ethylene glycol	107-21-1				1.0 %
Diethylene Glycol		1022			1.0 %

- Hazardous Substances List (MN-ERTK)

Name of substance	CAS No	References	Remarks
ethylene glycol	107-21-1	A	particulate vapor
Diethylene Glycol	111-46-6	I	

Legend

A American Conference of Governmental Industrial Hygienists (ACGIH), "Threshold Limit Values for Chemical Substances and Physical Agents and Biological Exposure Indices for 1992-93", available from ACGIH
I American Industrial Hygiene Association (AIHA), "Workplace Environmental Exposure Level Guides" (1992), available from AIHA

- Hazardous Substance List (NJ-RTK)

Name of substance	CAS No	Remarks	Classifications
ethylene glycol	107-21-1		
2-ethylhexanoic acid	149-57-5		
Diethylene Glycol			

- Hazardous Substance List (Chapter 323) (PA-RTK)

Name acc. to inventory	CAS No	Classification
1,2-ETHANEDIOL	107-21-1	E
ETHANOL, 2,2'-OXYBIS-	111-46-6	
GLYCOL ETHERS		E



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Prestone® Antifreeze/Coolant with Leak Detect

Version number: 1.0

Date of compilation: 2025-04-29

Legend

E Environmental hazard

- Hazardous Substance List (RI-RTK)

Name of substance	CAS No	References
ethylene glycol	107-21-1	T, F
Diethylene Glycol	111-46-6	F

Legend

F Flammability (NFPA®)

T Toxicity (ACGIH®)

California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987

Proposition 65 List of chemicals					
Name of substance	Name acc. to inventory	CAS No	Wt%	Remarks	Type of the toxicity
ethylene glycol	ethylene glycol (ethanediol)	107-21-1	48.59		developmental

VOC content

- Regulated Volatile Organic Compounds (VOC-EPA) 1.33 %
- Regulated Volatile Organic Compounds (VOC-Cal ARB) 0.1289 %

Industry or sector specific available guidance(s)

NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

Category	Rating	Description
Chronic	*	chronic (long-term) health effects may result from repeated overexposure
Health	1	irritation or minor reversible injury possible
Flammability	1	material that must be preheated before ignition can occur
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Category	Degree of hazard	Description
Flammability	1	material that must be preheated before ignition can occur
Health	1	material that, under emergency conditions, can cause significant irritation
Instability	0	material that is normally stable, even under fire conditions
Special hazard		



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Prestone® Antifreeze/Coolant with Leak Detect

Version number: 1.0

Date of compilation: 2025-04-29

National inventories

Country	Inventory	Status
AU	AIIC	all ingredients are listed
CA	DSL	all ingredients are listed
CN	IECSC	all ingredients are listed
EU	ECSI	not all ingredients are listed
EU	REACH Reg.	not all ingredients are listed
JP	CSCL-ENCS	not all ingredients are listed
JP	ISHA-ENCS	not all ingredients are listed
KR	KECI	all ingredients are listed
MX	INSQ	not all ingredients are listed
NZ	NZIoC	all ingredients are listed
PH	PICCS	all ingredients are listed
TR	CICR	not all ingredients are listed
TW	TCSI	all ingredients are listed
US	TSCA	all ingredients are listed (ACTIVE)

Legend

AIIC	Australian Inventory of Industrial Chemicals
CICR	Chemical Inventory and Control Regulation
CSCL-ENCS	List of Existing and New Chemical Substances (CSCL-ENCS)
DSL	Domestic Substances List (DSL)
ECSI	EC Substance Inventory (EINECS, ELINCS, NLP)
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China
INSQ	National Inventory of Chemical Substances
ISHA-ENCS	Inventory of Existing and New Chemical Substances (ISHA-ENCS)
KECI	Korea Existing Chemicals Inventory
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg.	REACH registered substances
TCSI	Taiwan Chemical Substance Inventory
TSCA	Toxic Substance Control Act

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information, including date of preparation or last revision

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
49 CFR US DOT	49 CFR U.S. Department of Transportation
ACGIH®	American Conference of Governmental Industrial Hygienists
ACGIH® 2024	From ACGIH®, 2024 TLVs® and BEIs® Book. Copyright 2024. Reprinted with permission. Information on the proper use of the TLVs® and BEIs®: http://www.acgih.org/tlv-bei-guidelines/policies-procedures-presentations/tlv-bei-position-statement
Acute Tox.	Acute toxicity
ATE	Acute Toxicity Estimate

Prestone® Antifreeze/Coolant with Leak Detect

Version number: 1.0

Date of compilation: 2025-04-29

Abbr.	Descriptions of used abbreviations
Cal/OSHA PEL	California Division of Occupational Safety and Health (Cal/OSHA): Permissible Exposure Limits (PELs)
Cal ARB	California Air Resources Board
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DEP CODE	Department of Environmental Protection Code
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
ED	Endocrine disruptor
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EPA	Environmental Protection Agency. An agency of the federal government of the United States charged with protecting human health and the environment
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
HHS	Higher hazard substance
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods Code
LHS	Lower hazard substance
NFPA®	National Fire Protection Association (United States)
NIOSH REL	National Institute for Occupational Safety and Health (NIOSH): Recommended Exposure Limits (RELS)
NLP	No-Longer Polymer
NPCA-HMIS® III	National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition
OSHA	Occupational Safety and Health Administration (United States)
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
Repr.	Reproductive toxicity
RTECS	Registry of Toxic Effects of Chemical Substances (database of NIOSH with toxicological information)
STEL	Short-term exposure limit
STOT RE	Specific target organ toxicity - repeated exposure
TLV®	Threshold Limit Values
TWA	Time-weighted average
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative

Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IM-DG). Dangerous Goods Regulations (DGR) for the air transport (IATA).



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Prestone® Antifreeze/Coolant with Leak Detect

Version number: 1.0

Date of compilation: 2025-04-29

Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H302	Harmful if swallowed.
H332	Harmful if inhaled.
H360D	May damage the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.