



LOW ELECTRICAL CONDUCTIVITY FLUID HEAVY DUTY EV BATTERY SYSTEM



- This formulation is engineered for high electrical insulation to minimize the risk of thermal runaway in the event of fluid contact with battery systems
- Electrical conductivity: < 100 $\mu\text{S}/\text{cm}$
- Proprietary POAT inhibitor (Phosphate organic acid technology)
- Excellent corrosion protection for metals found in modern battery systems (including stainless steel, copper, brass, and aluminum)
- Meets ASTM D8566 and GB29743.2 EV specifications
- Compatibility: Heavy-duty electric vehicles with CAB flux aluminum components
- Diluted with high purity RO / DI water



By choosing **EVX™** products, you are choosing peace of mind. **EVX™** solutions have been developed and tested to ensure compatibility with dedicated indirect electric cooling systems in both battery electric and hybrid vehicles. **EVX™** super low conductivity fluids provide excellent chemical stability, extended corrosion protection and meet specific heavy duty vehicle standard for EG purity.

READY TO USE

ITEM #	PACK	UPC
36-354PRESEVX	3 x 3.78 L	6 20235 78242 9
36-359PRESEVX	208 L Drum	7 97496 88391 9
36-359-275PRESEVX	1,041 L Tote	7 97496 88392 6

PRESTONE® and PRESTONE COMMAND® are registered trademarks of Prestone Products LLC. EVX™ is a trademark of Rechem Inc. used under license. All other trademarks are those of their respective owners.



LEARN MORE: PRESTONECOMMAND.COM
CONTACT US: CUSTOMERSERVICE@RECOHEM.COM
1-800-361-6030